

**参考**

※仕様、外観は参考です。  
商品改良のため予告なく変更することがあります。  
ご了承ください。

# RG6+Messenger-CS660BVM 75 Ohm Coaxial Cable Drop Cable

## PRODUCT DESCRIPTION:

BONDED LAMINATED ALUMINUM TAPE, 60% BRAID,  
BLACK PVC JACKET, 0.051" MESSENGER

### CENTER CONDUCTOR:

18 AWG COPPER-CLAD STEEL  
NOMINAL DIAMETER: 0.040" (1.02 mm)

### DIELECTRIC:

GAS EXPANDED POLYETHYLENE  
NOMINAL DIAMETER OVER DIELECTRIC: 0.180" (4.57 mm)

### SHIELD:

1<sup>ST</sup> SHIELD: LAMINATED ALUMINUM TAPE BONDED TO  
THE DIELECTRIC  
NOMINAL DIAMETER OVER TAPE: 0.187" (4.75 mm)

2<sup>ND</sup> SHIELD: 34 AWG ALUMINUM BRAID WIRE  
60% COVERAGE

### JACKET:

BLACK PVC  
NOMINAL DIAMETER OVER JACKET: 0.272" (6.91 mm)  
NOMINAL JACKET THICKNESS: 0.030" (0.76 mm)

### MESSENGER:

NOMINAL DIAMETER OF MESSENGER: 0.051" (1.30 mm)  
MINIMUM BREAKING STRENGTH: 170 lbf (77.1 kgf)

Center Conductor

Dielectric

Bonded Laminated  
Aluminum TapeAluminum  
Braided Shield

Steel Messenger

Jacket



## ELECTRICAL PROPERTIES:

IMPEDANCE: 75.0 ± 3.0 Ohms  
VSWR (10-1200 MHz): 1.2 MAX.  
VELOCITY OF PROPAGATION: 82% NOMINAL  
ATTENUATION: @ 68°F (20°C)

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.67 dB	2.20 dB
55 MHz	1.60 dB	5.25 dB
211 MHz	3.05 dB	10.00 dB
250 MHz	3.30 dB	10.82 dB
270 MHz	3.37 dB	11.04 dB
300 MHz	3.55 dB	11.64 dB
330 MHz	3.74 dB	12.26 dB
350 MHz	3.85 dB	12.63 dB
400 MHz	4.15 dB	13.61 dB
450 MHz	4.40 dB	14.43 dB
500 MHz	4.66 dB	15.29 dB
550 MHz	4.90 dB	16.08 dB
600 MHz	5.10 dB	16.73 dB
750 MHz	5.65 dB	18.54 dB
870 MHz	6.11 dB	20.04 dB
1000 MHz	6.55 dB	21.49 dB
1200 MHz	7.18 dB	23.55 dB
1500 MHz	8.13 dB	26.68 dB
2000 MHz	9.50 dB	31.17 dB
2500 MHz	10.73 dB	35.20 dB
3000 MHz	11.86 dB	38.91 dB
3224 MHz	12.68 dB	41.56 dB

STANDARD COMPLIANCE: ANSI/SCTE 74 2011